



株式会社 ミラプロ
MIRAPRO CO.,LTD.

MIRAPRO CHILLER— 제공가능한 제품LIST

	Type-A	Type-B	Type-C	Type-D	Type-E	Type-F
Temperature Control Range	-70°C ~ 145°C	-70°C ~ 30°C	10°C ~ 30°C	0°C ~ 60°C	0°C ~ 80°C	10°C ~ 80°C
	(Control accuracy +/- 1.0°C)	(Control accuracy +/- 0.5°C)	(Control accuracy +/- 0.5°C)	(Control accuracy +/- 0.5°C)	(Control accuracy +/- 0.5°C)	(Control accuracy +/- 0.5°C)
Cooling Capacity	8KW at -63°C	400W at -70°C	50KW	750W at 10°C	800W at 20°C	1000W at 20°C
		700W at -50°C				
Flow rate/Pressure	35L/min 0.75MPa at -60°C	9L/min 0.26MPa	100L/min 0.5MPa	10L/min 0.4MPa	8L/min 0.3MPa	8L/min 0.3MPa
Max Energy Consumption	49KVA	3.2KW	4.0KW	3.5KW	2.4KW	2.2KW
		(at -70°C stable)				
Tank Capacity	10.0L	7.2L	80L	12L	18.7L	12L
	(Use 5.5L)	(Use 4.5L)	(Use 40L)	(Use 9.5L)	(Use 12L)	(Use 6.5L)
Size	W1030 x D1530 x H1760	W580 x D800 x H1180	W550 x D850 x H1130	W500 x D680 x H1070	W480 x D580 x H790	W410 x D680 x H815

본사 · 본사공장 〒408-0111 야마나기현 호쿠토시 스타마쵸
아나다이라1100
본사TEL 0551-42-5111 FAX 0551-42-4311
영업부 직통 TEL 0551-42-5555 FAX 0551-42-5556